



MELTERS FDX 45 / 100 - SIMPLE AND DOUBLE



FDX



Touch screen control

- ✓ Independent temperature control for each tank
- ✓ Brewer start-up
- ✓ Programming and delayed start
- ✓ Eco night mode
- ✓ Adjustable stirrer speed
- ✓ Pump management (optional)

Drainage by GLACE valve

- ✓ 100% airtight closure
- ✓ Lockable outlet
- ✓ No plugs at the outlet



MELTERS FDX 45 / 100 - SIMPLE AND DOUBLE

USING: Store and maintain the masses at the desired temperature and homogeneity

PRODUCT: Chocolate - storage and melting

CAPACITY PER TANK : 45 and 100 kg

TANK

- Stainless steel construction. Insulated tank with brushed stainless steel lining.
- Stainless steel frame mounted on 4 castors or adjustable jacks.
- Single-shell tank with reinforced flat bottom.
- The stirrer is driven by a central sleeve welded to the bottom of the tank, making it 100% watertight.
- Top: Fully opening lid with "stop opening" safety device.
- Drainage: By heated manual ice valve with locking mechanism. Height to floor: 400 mm.
- Independent electric heating per tank.



simple or double tank

MALAXER

- Easily dismantled pendulum stirrer in the form of 2 ½ anchors welded to a central nut.

DRIVE UNIT

- Gear motor unit mounted under each tank.

ELECTRICAL EQUIPMENT

- Touch screen control
- Management by electromechanical control
- Automatic stirring function
- Optional pump control

CHARACTERISTIQUES :

Tension : 230/400 volts, 50 Hz.

Power : Simple 2.6 to 4.6 KW – Double 5.2 to 9.2 KW



OPTION :

Pump and piping for automatic feeding of a tempering or coating machine

DIMENSIONS :

	FDX 45 SIMPLE	FDX 45 DOUBLE	FDX 100 SIMPLE	FDX 100 DOUBLE
Width	600	1020	600	1020
Depth	680	680	680	680
Height	1460	1460	1860	1860
Charging height	950	950	1250	1250
Weight	60 kg	80 kg	72 kg	95 kg