



MELTERS

**Double tank melter****Driving screen**

CAPACITIES: FROM 45 to 200 kg
SINGLE OR DOUBLE TANK

Store and maintain the chocolate at the
desired temperature and homogeneity

ADVANTAGES

- + Touch screen programming**
- + Space-saving**
- + Easy cleaning**
- + Homogeneous melting**

Independent control per tank:

- **Temperatures**
- **Brewer speed**
- **Delayed start**
- **Night eco mode**
- **Pump (optional)**



MELTERS

TANK

- Stainless steel construction
- Insulated tank with brushed stainless steel coating
- Stainless steel frame mounted on 4 adjustable casters or jacks
- Single shell tank with reinforced flat bottom
- Drive of the brewer via a central sleeve welded at the bottom of the tank which makes it 100% waterproof
- Top: Fully opening lid with "stop opening" safety device
- **Drainage: By manually operated heated butterfly valve with lock on closing**
- Height of the valve from the ground: 400 mm
- Independent electric heating per tank



BREWER

Easily removable pendulum brewer in the shape of 2 ½ anchors welded to a central nut.

EQUIPMENT

- Touch screen control
- Management by electromechanical control
- Automatic brewing function
- *Optional pump control*

Pump and piping for automatic feeding of a tempering machine or coater.



Single or double tank

TECHNICAL INFO

Models	FDX 45 simple	FDX 45 double	FDX 100 simple	FDX 100 double
Capacity	45 kg	90 kg	100 kg	200 kg
Width	500 mm	970 mm	500 mm	970 mm
Depth	650 mm	650 mm	650 mm	650 mm
Height	1112 mm	1112 mm	1480 mm	1480 mm
Loading height	900 mm	900 mm	1160 mm	1160 mm
Weight	60 kg	80 kg	72 kg	95 kg
Tension	230 V single	400 V three	230 V single	400 V three
Power	2600 W	4600 W	5200 W	8000 W