FOR 50 YEARS, MADE IN FRANCE

MAGIC TEMPER ALPHA - 1.5K - 3K

OFFICIAL PARTNER

STATICE TEMPERING®



Magic Temper ALPHA

2 x 250 gr





Magic Temper 1.5K

1.5 kg



Magic Temper 3K

3 kg

TEMPERING BY SEEDING



Solid cocoa butter



Transformation



Stable crystals ready to seed your masses



Discover in video

FOR 50 YEARS, MADE IN FRANCE

OFFICIAL PARTNER

STATICE TEMPERING®

MAGIC TEMPER ALPHA - 1.5K - 3K

FUNCTIONING



The MAGIC TEMPER allows you to easily temper chocolate masses, couvertures, pralines, ganaches and fillings. The device is used for batch tempering for daily productions of 70 to 600 kg.
It is intended for artisan chocolate confectioners and R&D centers in industry. The frames are ready to be cut in 1 to 3 hours instead of 12 or 24 hours. With the MAGIC TEMPER, tempering is fast and 100% safe.

PERFORMANCES



- Seeding with stable polymorphic forms (faster crystallization)
- Better quality of textures, reduced risk of whitening, better shine
- Easy and reproducible tempering of couvertures, pralines and ganaches
- LCD display of regulation information (1.5K and 3K)
- Magic Temper ALPHA controllable by smartphone via dedicated application
- Tempering of interiors for one shot, dosing or extrusion
- Avoids aroma contamination linked to tempering on marble
- Cover with heat shield to ensure perfect homogeneity
- Secure digital regulation: no risk of liquid phase
- Tank adjustment range: from +30.0 °C to +35.0 °C / Adjustment accuracy: 0.1 °C
- Possibility of casting pralines at higher temperatures
- Artisanal and industrial quantities: volume from 2 x 250 gr to 3 kg
- Easy cleaning: radiated tank bottom and exterior surfaces



TECHNICAL INFO

MODELS	ALPHA	1.5K	3K
Capacity	2 x 250 gr	1.5 kg	3 kg
Option		Bluetooth and USB connectivity	Bluetooth and USB connectivity
Tank	Food grade aluminum	Food grade aluminum	Food grade aluminum
Waterproofing	IP21	IP21	IP21
Dimensions	D200 mm skin 100 mm	237 x 277 x 292 mm	237 X 277 X 412 mm
Weight	2 kg	4.5 kg	6.2 kg
Power	100V/240V power adapter	100V/240V power adapter	100V/240V power adapter
Tension	single phase 50/60 Hz – 12 V	single phase 50/60 Hz – 12 V	single phase 50/60 Hz – 12 V



www.savy-goiseau.com +33 (0)1 34 90 90 00 contact@savy-goiseau.com