SAVY hacos

FOR 50 YEARS, MADE IN FRANCE

COOLING TUNNELS

TRANSPLEX



- **Width to choose from:**
  180 / 220 or 300 mm
- **Length to choose from:**
  4m - 6m - 8m - 10m - 12m ou +
- **Removable deflectors for directing cold air**

Adaptable to all coating machines



Discover in video

FOR 50 YEARS, MADE IN FRANCE

TRANSPLEX COOLING TUNNELS

FUNCTIONING

The speed of air circulation in the ducts is optimized with cooling under the belt.
All models are equipped with a paper dispenser for handling products with transfers that require a longer cooling time.



The products are taken off:

- Either by passing the strip over an output receiving plate which allows the bonbons to be picked up for packaging with ergonomics designed to facilitate the working position.

To save space, the receiving plate assembly is easily removable when the tunnel is not in use.

- Either by passing the bonbons over two strips allowing easy removal of the products. The tunnels are delivered with removable baffles for working in radiation. In this case, the air is no longer directly on the bonbons, which facilitates the passage of products with transfers.



EQUIPMENT

- Stainless steel frame and conveyor
- Transparent PETG cooling boxes
- Adjusting belt speed
- Adjusting the temperature of the refrigeration unit
- Removable baffles for radiation work

TECHNICAL INFO

Model	Tunnel length	Cooling length	Width of belt	Total width	High. work	Input table length	Removable exit table length	Power	Tension
TP4DF	**5.5 m**	**2 m**	**180/220/300 mm**	**550 mm**	**1 m**	**0.75 m**	**0.50 m**	**2500W**	**230 V single-phase**
TP6DF	**7.5 m**	**6 m**	**180/220/300 mm**	**550 mm**	**1 m**	**0.75 m**	**0.50 m**	**2500W**	**230 V single-phase**
TP8DF	**10 m**	**8 m**	**180/220/300 mm**	**550 mm**	**1 m**	**0.75 m**	**0.50 m**	**2500W**	**230 V single-phase**